

PRODUCT SPECIFICATION SHEET**PRODUCT INFORMATION**

| | | | |
|-------------------------------|--------------|---------------|-----------------|
| Style: | I2459 | | |
| Sizing: | <u>Size</u> | <u>Part #</u> | <u>Overedge</u> |
| | Small | I2459S | Red |
| | Medium | I2459M | Green |
| | Large | I2459L | Brown |
| | XLarge | I2459XL | Navy Blue |
| XXLarge | I2459XXL | Black | |
| Registered Brand Name: | FlexTech™ | | |
| Classification: | Impact | | |

**PRODUCT DESCRIPTION**

| | |
|--------------------------------|--|
| Description: | Seamless Knit Palm Coated Glove with Impact Pads |
| Color: | Gray Shell / Black Palm / Orange TPR |
| Shell: | Blend of High Performance Fibers and Steel |
| Palm Coating: | Sandy Nitrile |
| Sold by: | Dozen Pair |
| Packaging (Inner Pack): | 12 Pairs |
| Packaging (Case Pack): | 72 Pairs |

CUT PROTECTION PERFORMANCE INFORMATION

| | |
|----------------------|---------------------------------------|
| Test Method: | ASTM F1790-97 |
| Test Results: | 4314 grams / 9.51 lbs ANSI Level 5 |
| Test Method: | ASTM F2992-15 |
| Test Results: | 4612 grams ANSI Level A7 |

ABRASION PROTECTION PERFORMANCE INFORMATION

| | |
|----------------------|----------------------------|
| Test Method: | ASTM D3884-05 |
| Test Results: | ANSI Level 4, 4,466 cycles |

CE EN 388 STANDARD

| | | |
|--------------------------------|-------|---------|
| EN Abrasion Resistance: | § 6.1 | Level 4 |
| EN Cut Resistance: | § 6.2 | Level 5 |
| EN Tear Resistance: | § 6.3 | Level 4 |
| EN Puncture Resistance: | § 6.4 | Level 3 |

WASHING INSTRUCTIONS

Machine wash in warm water with detergent or soap for 10-15 minutes. Water temperature should not exceed 140°F (60°C). Rinse in cold water. Tumble dry low for 15-20 minutes, not exceeding 120°F (50°C). For heavily soiled gloves pre-treat with a stain remover. Do not use bleach or dry cleaning solution.

CAUTION

Gloves are cut resistant but are not cut or puncture-proof. Do not subject to high-speed, serrated blades or intentional slashings.