

PRODUCT INFORMATION

Style: I2469

Sizing:	<u>Size</u>	<u>Part #</u>	<u>Overedge</u>
	Small	I2469S	Red
	Medium	I2469M	Green
	Large	I2469L	Brown
	XLarge	I2469XL	Navy Blue
	XXLarge	I2469XXL	Black



Registered Brand Name: FlexTech™
Classification: Impact

PRODUCT DESCRIPTION

Description: 15-Gauge Seamless Knit Palm Coated Glove with Impact Pads and Thumb Crotch
Color: Hi-Viz Yellow Shell / Black Palm / Orange TPR
Shell: Blend of High Performance and Cooling Fibers
Palm Coating: Sandy Nitrile
Sold by: Dozen Pair
Packaging (Inner Pack): 6 Pairs
Packaging (Case Pack): 72 Pairs

CUT PROTECTION PERFORMANCE INFORMATION

Test Method: ASTM F2992-15
Test Results: 1847 grams
ANSI Level A4

CE EN 388 STANDARD

EN Abrasion Resistance:	§ 6.1	Level 4
EN Cut Resistance:	§ 6.2	Level 5
EN Tear Resistance:	§ 6.3	Level 4
EN Puncture Resistance:	§ 6.4	Level 3

ABRASION PROTECTION PERFORMANCE INFORMATION

Test Method: ASTM D3884-05
Test Results: ANSI Level 4 > 3,000 cycles

WASHING INSTRUCTIONS

Machine wash in warm water with detergent or soap for 10-15 minutes. Water temperature should not exceed 140°F (60°C). Rinse in cold water. Tumble dry low for 15-20 minutes, not exceeding 120°F (50°C). For heavily soiled gloves pre-treat with a stain remover. Do not use bleach or dry cleaning solution.

CAUTION

Gloves are cut resistant but are not cut or puncture-proof. Do not subject to high-speed, serrated blades or intentional slashings.