

PRODUCT INFORMATION

Style:	Y9216		
Sizing:	<u>Size</u>	<u>Part #</u>	<u>Overedge</u>
	XSmall	Y9216XS	Yellow
	Small	Y9216S	Red
	Medium	Y9216M	Green
	Large	Y9216L	Brown
	XLarge	Y9216XL	Navy Blue
	XXLarge	Y9216XXL	Black
Registered Brand Name:	FlexTech™		
Classification:	Palm Dip		



PRODUCT DESCRIPTION

Description:	Seamless Knit Palm Coated Glove
Color:	Gray Shell / Black Palm
Shell:	Blend of High Performance Fibers and Steel
Palm Coating:	Sandy Nitrile
Sold by:	Dozen Pair
Packaging (Inner Pack):	12 Pairs
Packaging (Case Pack):	144 Pairs

CUT PROTECTION PERFORMANCE INFORMATION

Test Method:	ASTM F1790-97
Test Results:	3898 grams / 8.59 lbs. ANSI Level 5
Test Method:	ASTM F2992-15
Test Results:	4173 grams ANSI Level A7

ABRASION PROTECTION PERFORMANCE INFORMATION

Test Method:	ASTM D3389-10
Test Results:	ANSI Level 5 10,904 Cycles

CE EN 388 STANDARD

EN Abrasion Resistance:	§ 6.1	Level 4
EN Cut Resistance:	§ 6.2	Level 5
EN Tear Resistance:	§ 6.3	Level 4
EN Puncture Resistance:	§ 6.4	Level 4

WASHING INSTRUCTIONS

Machine wash in warm water with detergent or soap for 10-15 minutes. Water temperature should not exceed 140°F (60°C). Rinse in cold water. Tumble dry low for 15-20 minutes, not exceeding 120°F (50°C). For heavily soiled gloves pre-treat with a stain remover. Do not use bleach or dry cleaning solution.

CAUTION

Gloves are cut resistant but are not cut or puncture-proof. Do not subject to high-speed, serrated blades or intentional slashings.