

**PRODUCT INFORMATION**

<b>Style:</b>	<b>Y9236</b>		
<b>Sizing:</b>	<u>Size</u>	<u>Part #</u>	<u>Overedge</u>
	XSmall	Y9236XS	Yellow
	Small	Y9236S	Red
	Medium	Y9236M	Green
	Large	Y9236L	Brown
	XLarge	Y9236XL	Navy Blue
	XXLarge	Y9236XXL	Black
<b>Registered Brand Name:</b>	FlexTech™		
<b>Classification:</b>	Palm Dip		

**PRODUCT DESCRIPTION**

<b>Description:</b>	15-Gauge Seamless Knit Palm Coated Glove with Thumb Crotch
<b>Color:</b>	Hi-Viz Yellow Shell / Black Palm
<b>Shell:</b>	Blend of High Performance and Cooling Fibers
<b>Palm Coating:</b>	Sandy Nitrile
<b>Sold by:</b>	Dozen Pair
<b>Packaging (Inner Pack):</b>	12 Pairs
<b>Packaging (Case Pack):</b>	144 Pairs

**CUT PROTECTION PERFORMANCE INFORMATION**

<b>Test Method:</b>	ASTM F2992-15
<b>Test Results:</b>	1847 grams ANSI Level A4

**CE EN 388 STANDARD**

<b>EN Abrasion Resistance:</b>	§ 6.1	Level 4
<b>EN Cut Resistance:</b>	§ 6.2	Level 5
<b>EN Tear Resistance:</b>	§ 6.3	Level 4
<b>EN Puncture Resistance:</b>	§ 6.4	Level 3

**ABRASION PROTECTION PERFORMANCE INFORMATION**

<b>Test Method:</b>	ASTM D3389-10
<b>Test Results:</b>	ANSI Level 4 4,518 Cycles

**WASHING INSTRUCTIONS**

Machine wash in warm water with detergent or soap for 10-15 minutes. Water temperature should not exceed 140°F (60°C). Rinse in cold water. Tumble dry low for 15-20 minutes, not exceeding 120°F (50°C). For heavily soiled gloves pre-treat with a stain remover. Do not use bleach or dry cleaning solution.

**CAUTION**

Gloves are cut resistant but are not cut or puncture-proof. Do not subject to high-speed, serrated blades or intentional slashings.

Wells Lamont Industrial  
Toll-Free 1.800.247.3295 [www.wellslamontindustrial.com](http://www.wellslamontindustrial.com)