WELLS LAMONT Industrial

PRODUCT SPECIFICATION SHEET

PRODUCT INFORMATION

| Style: | Y9240-VP | | | |
|---------------------------------|---|---------------------|-----------------------|--|
| o | <u>Size</u> | Part # | <u>Overedge</u> | |
| Sizing: | XSmall | Y9240XS-VP | Yellow | |
| | Small | Y9240S-VP | Red | |
| | Medium | Y9240M-VP | Green | |
| | Large | Y9240L-VP | Brown | |
| | XLarge | Y9240XL-VP | Navy Blue | |
| Registered Brand Name: | FlexTech™ | | | |
| Classification: | Palm Dip | | | |
| | PRO | DUCT DESCI | RIPTION | |
| Description: | Poly/Cotton Seamless Knit Palm Coated Glove | | | |
| Color: | Gray Shell / Blue Palm | | | |
| Shell: | Polyester/Cotton | | | |
| Palm Coating: | Crinkled Late | x | | |
| Sold by: | Dozen Pair | | | |
| Packaging (Inner Pack): | 12 Pairs | | | |
| Packaging (Case Pack): | 144 Pairs | | | |
| ABRASI | ON PROTEC | FION PERFO | RMANCE IN | FORMATION |
| Test Method: | ASTM D3389 | -05 | | |
| Test Results: | Level 4 >3,00 | 0 Cycles | | |
| | WASI | HING INSTRU | JCTIONS | |
| | low for 15-20 minut | es, not exceeding 1 | | re should not exceed 140°F (60°C). heavily soiled gloves pre-treat with a |
| | | CAUTION | | |
| This glove does not contain cut | resistant materials. | Do not use in condi | tions where cut pr | otection is needed. |
| | | Wells Lamont Indus | rial | |
| | Toll-Free 1.800 | | slamontindustrial.com | |