**WELLS LAMONT** PRODUCT SPECIFICATION SHEET

Industrial

PRODUCT INFORMATION

Y9282 Style:

Size Part # Overedge Sizing:

Small Y9282S Red Medium Y9282M Green Y9282L Large Brown XLarge Y9282XL Blue

Registered Brand Name: GuardTec 3 Classification: Palm Dip



Description: Seamless Cut Resistant Palm Coated Glove

Color: Gray

Shell: GuardTec Yarn Cut Resistant Shell

Palm Coating: Palm and Finger Tip Coated with Natural Foam Latex

Sold by: Dozen Pair Packaging (Inner Pack): 12 Pairs Packaging (Case Pack): 144 Pairs

## **CUT PROTECTION PERFORMANCE INFORMATION**

**Test Method:** ASTM F1790-97 Test Results: 1,165 grams / 2.57lbs.

ANSI Cut Level 3

Test Method: ASTM F2992-15 Test Results: 1,225 grams ANSI Level A3

**CE EN 388 STANDARD** 

EN Abrasion Resistance: Level 2 §6.1 Level 3 EN Cut Resistance: §6.2 EN Tear Resistance: Level 4 §6.3 EN Puncture Resistance: §6.4 Level 2

## ABRASION PROTECTION PERFORMANCE INFORMATION

**Test Method:** ASTM D3389-05 **Test Results:** Level 4 > 3,000 Cycles

## WASHING INSTRUCTIONS

Machine wash in warm water with detergent or soap for 10-15 minutes. Water temperature should not exceed 140°F (60°C). Rinse in cold water. Tumble dry low for 15-20 minutes, not exceeding 120°F (50°C). For heavily soiled gloves pre-treat with a stain remover. Do not use bleach or dry cleaning solution.

## CAUTION

Gloves are cut resistant but are not cut or puncture-proof. Do not subject to high-speed, serrated blades or intentional slashings.

Wells Lamont Industrial 6640 W Touhy Ave Niles IL 60714

Toll-Free 1.800.247.3295 Fax 1.847.470.1026 www.wellslamontindustrial.com

KM 03/18