WELLS LAMONT

Industrial

PRODUCT SPECIFICATION SHEET

## PRODUCT INFORMATION


Style: Y9284

Part # Size Overedge

Sizing:

XXSmall Y9284XXS Purple XSmall Y9284XS Yellow Small Y9284S Red Medium Y9284M Green Y9284L Brown Large XLarge Y9284XL Blue XXLarge Y9284XXL Black

Registered Brand Name: GuardTec 3 Classification: Palm Dip



Seamless Cut Resistant Palm Coated Glove Description:

Color: Gray

Shell: GuardTec Yarn Cut Resistant Shell

Palm Coating: Palm and Finger Tip Coated with Polyurethane

This Glove is Silicone Free

Sold by: Dozen Pair Packaging (Inner Pack): 12 Pairs Packaging (Case Pack): 144 Pairs

### **CUT PROTECTION PERFORMANCE INFORMATION**

Test Method: ASTM F1790-97 Test Results: 1,044 grams / 2.30lbs. ANSI Cut Level 3

Test Method: ASTM F2992-15 1039 grams Test Results:

ANSI Level A3

## **CE EN 388 STANDARD**

EN Abrasion Resistance: §6.1 Level 4 EN Cut Resistance: §6.2 Level 3 §6.3 EN Tear Resistance: Level 4 **EN Puncture Resistance:** Level 1 §6.4

# **ABRASION PROTECTION PERFORMANCE INFORMATION**

Test Method: ASTM D3389-10 Test Results: Level 4 7,774 Cycles

### WASHING INSTRUCTIONS

Machine wash in warm water with detergent or soap for 10-15 minutes. Water temperature should not exceed 140°F (60°C). Rinse in cold water. Tumble dry low for 15-20 minutes, not exceeding 120°F (50°C). For heavily soiled gloves pre-treat with a stain remover. Do not use bleach or dry cleaning solution.

#### CAUTION

Gloves are cut resistant but are not cut or puncture-proof. Do not subject to high-speed, serrated blades or intentional slashings.

Wells Lamont Industrial

Toll-Free 1.800.247.3295 www.wellslamontindustrial.com

© 2019 Wells Lamont Industrial, LLC - All rights reserved.

KM 3/19