WELLS LAMONT

Industrial

PRODUCT SPECIFICATION SHEET

PRODUCT INFORMATION

Style: Y9286

Size Part # Overedge

Sizing:

XSmall Y9286XS Yellow Small Y9286S Red Medium Y9286M Green Large Y9286L Brown XLarge Y9286XL Blue XXLarge Y9286XXL Black

Registered Brand Name: GuardTec 3
Classification: Palm Dip



Description: Seamless Cut Resistant Palm Coated Glove

Color: Gray

Shell: GuardTec Yarn Cut Resistant Shell

Palm Coating: Palm and Finger Tip Coated with Sandy Nitrile

Sold by: Dozen Pair Packaging (Inner Pack): 12 Pairs Packaging (Case Pack): 144 Pairs

CUT PROTECTION PERFORMANCE INFORMATION

Test Method: ASTM F1790-97
Test Results: 1,265 grams / 2.79 lbs

ANSI Cut Level 3

CE EN 388 STANDARD

EN Abrasion Resistance:§6.1Level 4EN Cut Resistance:§6.2Level 3EN Tear Resistance:§6.3Level 4EN Puncture Resistance:§6.4Level 2

ABRASION PROTECTION PERFORMANCE INFORMATION

Test Method: ASTM D3389-05
Test Results: Level 4 > 3,000 Cycles

WASHING INSTRUCTIONS

Machine wash in warm water with detergent or soap for 10-15 minutes. Water temperature should not exceed 140°F (60°C). Rinse in cold water. Tumble dry low for 15-20 minutes, not exceeding 120°F (50°C). For heavily soiled gloves pre-treat with a stain remover. Do not use bleach or dry cleaning solution.

CAUTION

Gloves are cut resistant but are not cut or puncture-proof. Do not subject to high-speed, serrated blades or intentional slashings.

Wells Lamont Industrial

Toll-Free 1.800.247.3295 www.wellslamontindustrial.com