

**PRODUCT INFORMATION**

**Style:** Y9290

**Sizing:** Small Y9290S  
Medium Y9290M  
Large Y9290L  
XLarge Y9290XL  
XXLarge Y9290XXL

**Registered Brand Name:** FlexTech™  
**Classification:** Palm Dip



**PRODUCT DESCRIPTION**

**Description:** Fully Coated Cut Resistant Palm Dip  
**Color:** Gray Shell / Black Palm  
**Shell:** 13 Gauge HPPE Cut Resistant Knit  
**Palm Coating:** Full NBR Coating and Sandy Nitrile Palm Coating

**Sold by:** Dozen Pair  
**Packaging (Inner Pack):** 12 Pairs  
**Packaging (Case Pack):** 144 Pairs

**CUT PROTECTION PERFORMANCE INFORMATION**

**Test Method:** ASTM F1790-97  
**Test Results:** 4.46 lbs. / 2,202 grams  
**ANSI Level** 4

**ABRASION PROTECTION PERFORMANCE INFORMATION**

**Test Method:** ASTM D3389-10  
**Test Results:** ANSI 4 6,099 Cycles

**PUNCTURE PERFORMANCE INFORMATION**

**Test Method** EN388:2003  
**Test Results** 126N  
**ANSI Level** 4

**CE EN 388 STANDARD**

**EN Abrasion Resistance:** § 6.1 Level 4  
**EN Cut Resistance:** § 6.2 Level 5  
**EN Tear Resistance:** § 6.3 Level 4  
**EN Puncture Resistance:** § 6.4 Level 3

**WASHING INSTRUCTIONS**

Machine wash in warm water with detergent or soap for 10-15 minutes. Water temperature should not exceed 140°F (60°C). Rinse in cold water. Tumble dry low for 15-20 minutes, not exceeding 120°F (50°C). For heavily soiled gloves pre-treat with a stain remover. Do not use bleach or dry cleaning solution.

**CAUTION**

Gloves are cut resistant but are not cut or puncture-proof. Do not subject to high-speed, serrated blades or intentional slashings.